

Welcome!

The program will begin soon.
You will not hear audio until we begin.

Automated Well Control Value Proposition

DSATS Presentation

Bryan Atchison – Safe Influx Ltd

SPE Webinars are Sponsored by:

SPE
SPE Foundation

System Overview




Overall Philosophy


- Uses existing rig monitoring equipment as input for Influx Detection
- Interfaces with, and controls, existing rig drilling equipment
- Existing Rig Safety Systems remain fully functional
- Can be installed on both Conventional and Cyber based Drilling Systems
- Efficient installation process minimizing impact on operations

System Design

- Small Footprint (PLC Cabinet and HMI Screen)
- Easy Interface with Existing Drilling Controls Systems
- Interface arrangements to stay in place for future re-instatement



PLC Cabinet




HMI Screen

System Installation


- Rig Survey 2 Persons for 2-3 days (no impact on Operations)
- Design / Fabrication 3-4 months (driven by PLC supply)
- Installation / Commissioning 2 Persons for 2-4 days (limited impact on operations, most can be done off-line)
- Training 1/2-day (Driller, Tool Pusher, AD as a minimum)



System Topology



Product Assurance



Why Automated Well Control?



Drillers' loss of Level 1 Situational Awareness (loss of attention) causes **up to 67% of blowouts**.

Loss of Well Control frequency is **6.04 wells/1000** for exploration wells in US Gulf of Mexico.



71% of Well Control Incidents caused by Human Factors.

Loss of Well Control frequency is **1.50 wells/1000** for exploration wells in a North Sea Standard operation.




Petroleum Safety
Authority Norway

The triggering causes of 54% of kicks could be mitigated or prevented by EKDS and automated response.



Why Automated Well Control?

Key Control Loops




ABS and Dynamic Stability Control



- Automated Braking Feature.
- Allowing the driver to maintain more control over the vehicle.
- Maintains Stability, avoid hazards and improves safety.
- ABS is required on all new passenger cars sold in the EU since 2004.



Reduction in Influx Volume




Operational Efficiency




Source: SPE 167990

Well Control Incidents Timeline





Comparative Human Factors Analysis



94%
**Reduction in
Probability of
Human Error**



Contributing Factors to an Influx



79% of incidents fall into categories that are influenced by human behaviour. Over 10% of these incidents escalate into uncontrolled events


Total Cost of Risk- Well Control



Input Data:	
COST INFORMATION	
Spread Rate (Time dependent Costs) \$/day	500
Insurance Cost as percentage of Asset	2.0%
Insurance saving using Safe Influx	10%
Average number of wells drilled/year	4
BLOWOUTS	
Blowouts /1000 wells	4
Blowouts that lead to Damage /Total Loss	See Note
Total Loss: Rig Value \$M	400
Non Total Loss: Repairable Damage \$M	200
Damage to Reputation: Total Loss \$M	400
Damage to Reputation: Repairable Damage \$M	200
KICKS	
Kicks /well	0.6
Days for Kick Recovery per incident	6
Kick Recovery Time:Safe Influx vs Manual	20%
ENVIRONMENTAL SPILLS	
Chance of Medium Spill per Blowout	0.016
Chance of Major Spill per Blowout	0.056
Cost to clean up Spill \$M	5000
LOSS OF LIFE	
Chance of loss of life per blowout	0.400
Cost of life lost \$M	10
HUMAN FACTORS	
Human Factors reduction %	70%



Reduction in Risk



*Reduced
Risked Costs*

- Reduced Insurance Exposure
- Reduced Risk/Cost of Blowout
- Reduced Kick Recovery Time



Key Points

Cost of Risk often not articulated in well AFE




Potential for up to **50% Risk Cost Savings** per well with Automated Well Control

TCoR Model could include NPV of deferred / lost production

TCOR – Well Control Events – Per Well



Optimize Well Design



- Influx Volume**
 - Reduced Volume
 - Consistent & Repeatable
- Pressures**
 - Reduced Well Pressures
 - Reduced Surface Pressure
- Casing Design**
 - Reduction in Kick Tolerance



How to reduce risk with Automated Well Control?



Reduced Well Control Risks

Reduction in probability of human error.
Robust decision-making, efficiency and safety

Cost Effective Wells

Reduced influx volumes.
Reduced Total Cost of Risk for well control.
Reduced well construction cost.

TCOR Model




\$\$\$


Optimize
Well Design



The Journey Ahead



Environmental Gains towards Net Zero



NET ZERO



Large reduction in
blowouts and
environmental spills

Reduction in carbon
footprint and
greenhouse gas -
faster recovery from
(smaller) kicks

Potential for more
efficient well designs
and smaller carbon
footprint, up to 20%
less



Summary



Reduced Well Control Risks

Reduction in probability of human error by 94%
Robust decision-making, efficiency and safety

Environmental Performance

Reduced spills
Reduced carbon footprint

Cost Effective Wells

Reduced influx volumes
Reduced Total Cost of Risk for well control by 50%
Reduced well construction costs by 20%




Conclusions



Five times faster = cost effective wells



Driller-assist tool – no extra personnel




All kicks in all wells safely detected and managed



De-scoping well design



Simple and short rig installation process



Well control assurance

Safe Influx Automated Well Control


Protection against blowouts
Risk and cost reduction
Peace of mind

www.safeinflux.com

Bryan Atchison, Managing
Director
T. +44 (0) 7912 242421
bryan.atchison@safeinflux.com



False Positives Filters



Drillers HMI

